

## **ENKLO AP**

### **SPECIAL FEATURES**

Enklo AP grades are Hydraulic and Circulating Oils blended from mineral oils and suitable additives. It imparts good oxidation and anti-rust properties. It has got good demulsibility, chemical stability and anti-foam characteristics. This oil has moderate anti-wear properties.

### **APPLICATION AREA**

Enklo AP grades are suitable for Hydraulic Equipment operating under moderate conditions, which require a lubricant with mild anti-wear and EP properties. It is recommended for Hydraulic Systems, Enclosed Gear Boxes, Air Compressors, Chain Drives, Bearings and Vacuum Pumps. It ensures longer equipment life and low maintenance costs.

### **SPECIFICATION**

It meets the requirements of IS: 3098 – 1983 (reaffirmed 1993).

### **PHYSICO CHEMICAL PROPERTIES**

<b>Parameters</b>	<b>VG 68</b>	<b>VG 150</b>
Appearance	Bright & Clear	Bright & Clear
Viscosity, Kinematic @ 40°C, cSt	68	150
Viscosity Index, Min	90	90
Flash Point, COC, °C, Min	210	230
Pour Point, °C, Max	0	0
Copper Strip Corrosion @ 100°C for 3 hrs, Max	1	1

### **PACKAGES**

The product is available in 20 ltr (HDPE) drums.