

## **CRUSHWELL**

### **SPECIAL FEATURES:**

CRUSHWELL SERIES OF LUBRICANTS ARE SUGAR MILL LUBRICANTS MANUFACTURED FROM HIGH VISCOSITY LUBRICATING OIL BASE STOCKS AND CONTAIN SELECTED NON-TOXIC MILD EP AND SPECIAL COMPOUNDING AGENTS TO ENSURE LUBRICATION EVEN IN PRESENCE OF JUICE. THESE OILS PREVENT WEAR AND CORROSION OF BEARINGS AND HAVE EXCELLENT RESISTANCE TO LEAKAGE.

### **APPLICATION AREA:**

THESE ARE IDEAL LUBRICANTS MEETING REQUIREMENTS OF HEAVILY LOADED MILL ROLL BEARINGS IN SUGAR MILLS. THESE CARRY APPROVALS OF SUGAR MILL MACHINERY MANUFACTURERS. THESE OILS ARE ALSO RECOMMENDED IN CENTRALISED LUBRICATION SYSTEM OF SLOW SPEED SPUR AND HELICAL GEARS IN CERTAIN INDUSTRIES AND FOR OPEN GEAR LUBRICATION BY SLUSH PAN METHOD.

### **PHYSIOCHEMICAL PROPERTIES:**

| PARAMETERS                         | 2       | 3       | 4       |
|------------------------------------|---------|---------|---------|
| FLASH POINT, COC, °C, MIN.         | 204     | 204     | 204     |
| VISCOSITY, KINEMATIC, @ 100°C, cSt | 40 - 45 | 60 - 65 | 89 - 94 |

### **PACKAGES:**

210 LTS.(STEEL DRUMS).