

ALPROL N 100

SPECIAL FEATURES:

ALPROL N 100 IS A SUPERIOR GRADE OIL MANUFACTURED FROM SOLVENT REFINED MINERAL OILS AND FORTIFIED WITH SUITABLE ADDITIVES TO IMPART EXCELLENT PROPERTIES. THE INHERENT HIGH DEMULSIBILITY, CHEMICAL STABILITY AND ANTI-FOAM CHARACTERISTICS MAKE THIS GRADE AN APPROPRIATE CHOICE.

APPLICATION AREA:

ALPROL N 100 IS A MULTIPURPOSE LUBRICANT FOR APPLICATIONS LIKE HYDRAULIC SYSTEMS, GENERAL PURPOSE MACHINERY, MACHINE TOOLS AND GEARBOXES.

PHYSICOCHEMICAL PROPERTIES:

PARAMETERS	
APPEARANCE	BRIGHT & CLEAR
VISCOSITY, KINEMATIC cSt, (@100°C)	9.5 – 11.5
VISCOSITY INDEX, MIN	95
FLASH POINT (COC), °C, MIN	224
POUR POINT, °C, MAX.	0
COPPER STRIP CORROSION @ 100°C FOR 3 HRS., MAX	1

PACKAGES:

BULK SUPPLY ONLY