

HP CABLE JELLY OIL

SPECIAL FEATURES:

HP CABLE JELLY OIL IS A SUPERIOR GRADE OIL MANUFACTURED FROM HIGHLY SOLVENT REFINED MINERAL OILS AND FORTIFIED WITH SUITABLE ADDITIVES TO IMPART EXCELLENT PROPERTIES. THE INHERENT HIGH DEMULSIBILITY, CHEMICAL STABILITY AND ANTI-FOAM CHARACTERISTICS MAKE THESE GRADES AN APPROPRIATE CHOICE FOR ALL APPLICATION.

APPLICATION AREA:

HP CABLE JELLY OIL IS USED AS A RAW MATERIAL FOR MANUFACTURING OF CABLE JELLY. IT CAN ALSO BE USED FOR GENERAL PURPOSE LUBRICATION.

PHYSICOCHEMICAL PROPERTIES:

PARAMETERS	
APPEARANCE	BRIGHT & CLEAR
VISCOSITY, KINEMATIC cSt, (@ 100°C)	29.8 – 33.0
VISCOSITY INDEX, MIN	95
FLASH POINT (COC), °C, MIN	280
POUR POINT, °C, MAX.	(-)6
COPPER STRIP CORROSION @ 100°C FOR 3 HRS., MAX	1

PACKAGES:

BULK SUPPLY ONLY